

CONSTRUCTION

- Three piece – body, nut and serrated sleeve
- Manufactured from CA360 brass rod

ADVANTAGES

- Easy to assemble and dis-assemble
- No special hose preparation
- With or without spring guard

APPLICATIONS

- For air brake systems
- Pressure rating – 125 PSI
- Meets SAE and DOT specifications
- Used with SAE J1402 Air Brake Hose

ORDERING INFORMATION

- Fittings are supplied as assemblies consisting of body, nut and sleeve

ASSEMBLY

- Slide nut onto the hose
- Slide the tapered end of the sleeve onto the hose facing the fitting
- Insert hose completely into the fitting until it bottoms
- Nut is tightened until making contact with the body
- Do not reuse sleeves. Bodies and nuts should always be re-inspected

NOTES

- Current price list represents in stock cataloged items.
- Configurations and dimensions are subject to change without notice

360A HOSE SLEEVE

PART NUMBER	HOSE	A
360A-6	3/8	.69
360A-8	1/2	.69



361A HOSE NUT

PART NUMBER	HOSE	A	HEX
361A-6	3/8	1.18	13/16
361A-8	1/2	1.125	1-1/4




371A HOSE NUT WITH SPRING GUARD

PART NUMBER	HOSE	HEX
371A-6	3/8	13/16
371A-8	1/2	1-1/4




362A UNION

PART NUMBER	HOSE	A
362A-6	3/8	2.95
362A-8	1/2	2.96




368A HOSE CONNECTOR ASSEMBLY

PART NUMBER	HOSE	PIPE THREAD	A	HEX
368A-6B	3/8	1/4	2.25	1
368A-6C	3/8	3/8	2.38	1
368A-6D	3/8	1/2	2.44	1
368A-8C	1/2	3/8	2.24	1-1/8
368A-8D	1/2	1/2	2.40	1-1/8




378A HOSE CONNECTOR ASSEMBLY WITH SPRING GUARD

PART NUMBER	HOSE	PIPE THREAD	A	HEX
378A-6B	3/8	1/4	4.75	1
378A-6C	3/8	3/8	4.75	1
378A-6D	3/8	1/2	4.88	1
378A-8C	1/2	3/8	5.12	1-1/8
378A-8D	1/2	1/2	4.88	1-1/8



388A ADAPTER

PART NUMBER	STRAIGHT THREAD	PIPE THREAD	A	B	HEX
388A-12B	3/4-20	1/4	1.06	.31	3/4
388A-12C	3/4-20	3/8	1.12	.31	3/4
388A-14C	7/8-20	3/8	1.19	.44	7/8
388A-14D	7/8-20	1/2	1.38	.50	7/8



129A BULKHEAD ADAPTER FPT TO FPT

PART NUMBER	STRAIGHT THREAD	PIPE THREAD	A
129A-A	5/8-18	1/8 FPT	1.50
129AS-B	3/4-16	1/4 FPT	.92
129A-B	3/4-16	1/4 FPT	1.50
129A-C	1-14	3/8 FPT	1.32
129A-D	1 1/8-14	1/2 FPT	1.50

