



# Coded switches



<b>3 m PVC cable</b>			
Designation			MAK-5336-3
<b>Part number</b>			<b>649.0653.310</b>
Delivery: ex-stock/built to order			●/-
<b>6 m PVC cable</b>			
Designation			MAK-5336-6
<b>Part number</b>			<b>649.0653.311</b>
Delivery: ex-stock/built to order			●/-
<b>9 m PVC cable</b>			
Designation			MAK-5336-9
<b>Part number</b>			<b>649.0653.312</b>
Delivery: ex-stock/built to order			●/-
<b>Plug M 12/4 poles</b>			
Designation			MAK-5336-STK
<b>Part number</b>			<b>649.0653.313</b>
Delivery: ex-stock/built to order			●/-
<b>Switching capacity</b>			
Operating voltage	max.		DC 30 V
Switching capacity	max.		250 mW
<b>Ambient conditions</b>			
Temperatur range	min./max.		-5 °C/+70 °C +23 °F/+158 °C
Protection class (according to IEC 529, EN 60529)			IP 67
Housing material			PA 6.6
<b>Sensing distance</b>	S on	min.	3 mm
	S off	max.	10 mm
<b>Operating magnet</b>			
Designation			TK-43-CD
<b>Part number</b>			<b>640.2043.023</b>
To be used MÜZ			
see page			256-257

All dimensions in mm

Other versions available on request.

